


## 9060-5043T



### General Options

- Pressure Valve
- Humidity Indicator
- Padlock Wire
- Hinged Lid
- Coupling Ring
- Forklift Legs

### Colour Options



### General features

Suprobox cases have been made to withstand the toughest environmental and climatic conditions. The case is manufactured as a solid uniform structure which makes it extra resistant to impact and vibration enabling the case to be handled and transported in extreme situations. The polymer raw material resin is UV resistant and is specifically designed to function in extreme temperatures and under solar load. Ideal for electronics, memory storage equipment, servers, lab and testing equipment, medical equipment, aerospace equipment, broadcasting equipment, meteorological equipment, flight simulators, satellite communications, radars and mobile military equipment. R SERIES 194 different sizes RACK CASES 24 different sizes With over 200 sizes SUPROBOX offer one of the widest selections available in the market. Once placed in a Suprobox case, your delicate equipment and instruments are transported and used under complete protection from shock, vibration, moisture and impact. Your cases come furnished with the appropriate grade foam and/or shock mounting equipment in line with your special project requirements.

- Ruggedized case body made from impact resistant PE material
- Easy grip ruggedized stainless steel handles
- Stainless Steel, heavy duty catches
- Automatic pressure relief valve (standard)
- Waterproof silicone seal between body and lid
- Extra resistant to impact & vibration
- UV resistant
- Made to withstand extreme temperatures & solar load
- Optional rugged edge castors
- Custom internals available
- Color options
- Multibrix® stacking system (straight or cross stacking of same or different size cases)
- MIL-STD 810 G
- Dust and Water Protection rated IP 65/IP 67

### Product Specifications

External Dimensions LxWxH (Body & Lid)	: 900 x 600 x H 930 mm
Internal Dimensions LxWxH (Body & Lid)	: 810 x 510 x H 880 mm
Internal Volume	: 363,528 Lt
Body Outer Height	: H 500 mm
Lid Outer Height	: H 430 mm
Body Internal Depth	: H 480 mm
Lid Internal Depth	: H 400 mm
Weight	: ~ 0 kg
Corner Wheel	: Yes
Operating temperature	: °C min - 50 / max + 65
Standard Colors	: Black and Olive Drab